



**VCTEC**

**PIPE CONNECTORS**



# Pipe seals



## INFORMATION

Votec pipe connectors are made in EPDM rubber and are used as a transition between different types of pipes and dimensions.

Manufactured in accordance with EN 681-1 and has type approval no. 1122.

### Manufacturer's declaration

The production of this product has been carried out in accordance with the type-approval of the production control decision and the documents on which the type-approval decision has been based.



Type approval nr: 1122

## Votec Pipe seals

Art nr	Dimension mm	Drill hole mm
<b>2357520</b>	110	121

Use: For thin-walled connection.



**2357520**

Art nr	Dimension mm	Drill hole mm
<b>2357521</b>	160	171
<b>2357522</b>	200	210



**2357521**



**2357522**

## Telescopic collar

Art nr	Dimension
<b>2359331</b>	400 x 315, smooth riser
<b>2359338</b>	400 x 315, double-walled riser

Use: The collar is used to mount 315 telescopic tube in 400 well.



**2359331**



**2359338**

Art nr	Dimension
<b>2435243</b>	200 x 160, smooth riser

Use: The collar is used to mount 160 telescopic tube in 200 well.



**2435243**

## Installation instructions pipe connectors

1. Ensure that the pipe ends are free of miter residues and degrees.
2. Slide the pipe ends into the connector.
3. Density test the installation.

# Pipe seals



## Products

For connection of incoming conduit to well or pipeline.

Art nr	Dimension mm	Drill hole mm	Length mm	Internal seal grooves
The seal is without tube stop				
<b>2201009</b>	110	121	60	-
<b>2435244</b>	110	138	70	3 st
<b>2435248</b>	110	138	90	5 st
<b>2435245</b>	160	186	70	3 st
<b>2435249</b>	160	186	90	5 st
<b>2435247</b>	200	226	70	3 st
<b>2435250</b>	200	226	90	5 st
<b>2201010</b>	160	171	60	-
<b>2358706</b>	200	210	60	-
The seal is fitted with a tube stop				
<b>2435251</b>	110	127	60	-
<b>2435252</b>	160	177	60	-



**2201009**



**2435244**



**2435250**



**2435245**



**2435248**



**2201010**



**2435249**



**2435247**



**2358706**



**2435251**



**2435252**

## Hole saws

Art nr	Dimension
<b>2350117</b>	Hole saw Ø 127 x 100 mm
<b>2350118</b>	Hole saw Ø 138 x 100 mm
<b>2350123</b>	Hole saw Ø 172 x 100 mm
<b>2350119</b>	Hole saw Ø 177 x 100 mm
<b>2350120</b>	Hole saw Ø 186 x 100 mm
<b>2350124</b>	Hole saw Ø 212 x 100 mm
<b>2350121</b>	Hole saw Ø 226 x 100 mm

Novipro Hole saws with hardened tooth points and a cutting depth of 100 mm. They are specially developed for hole punching on plastic wells and drain pipes where a deeper hole saw is required. The hole saws are hand welded in a high quality piece of steel and are available in dimensions 127–226 mm.



Art nr	Dimension
<b>2350115</b>	Center drill in steel, 150 mm, spare part drill
<b>2350116</b>	Hole saw holder in A2 steel, thread 5/8 ", complete with drill bit

